





# Polk City Fire Department

## Standard Operating Guidelines

335b

---

---

### # 335 – Rescue 458 Seat Position Assignments

Date Issued: 09/06/2007

Date Last Revised: 1/31/2016

---

---

- Throw ground ladder(s)
- Provide ventilation
- Search and rescue (team leader)
- TOOLS UTILIZED:
  - SCBA, Thermal Imaging Camera, and handlight

#### 4) Water Supply

##### IF PERFORMING AS AN ENGINE COMPANY:

- Provides hydrant/water supply
- Assists with feeding initial hoseline to attack-line personnel
- Assist in stretching backup hoseline
- Serve as backup on backup line

##### IF PERFORMING AS A TRUCK COMPANY:

- Throw ground ladder(s)
- Provide ventilation
- Search and rescue
- TOOLS UTILIZED:
  - SCBA, ladder(s), irons, hand tools/ forcible entry tools, and portable radio

#### 5) Backup

##### IF PERFORMING AS AN ENGINE COMPANY:

- Assists with pulling initial attack line
- Backup on initial attack-line

##### IF PERFORMING AS A TRUCK COMPANY:

- Throw ground ladder(s)
- Provide ventilation
- Search and rescue
- TOOLS UTILIZED:
  - SCBA, irons, hand tools/ forcible entry tools, and portable radio

#### 6) Break Hose

##### IF PERFORMING AS AN ENGINE COMPANY:

- Break supply hose at rear of apparatus and assist driver with hookup
- Assists with feeding hoseline to initial attack-line personnel
- Pulls backup hoseline
- Serve as nozzleman on backup line (team leader)

##### IF PERFORMING AS A TRUCK COMPANY:

- Throw ground ladder(s)
- Provide ventilation
- Search and rescue



# Polk City Fire Department Standard Operating Guidelines

335c

---

---

## # 335 – Rescue 458 Seat Position Assignments

Date Issued: 09/06/2007

Date Last Revised: 1/31/2016

---

---

- TOOLS UTILIZED:

- SCBA, ladder(s), chainsaw (when necessary), and handlight

\*\* These seat assignments are recommendations and can be changed as the situation/ call warrants. While enroute to the call, communication between crew members of various job duties is essential.

Of the minimum four members assembled to begin interior operations, at least two members must remain outside the structure. These two outside members may be performing other duties while standing by, which may include, but are not limited to, actions such as the establishment of a water supply, the shutting off of utilities, the placement of ladders, the laying of the attack line to the entrance of the structure, or exposure protection, but must have full turn-out, SCBA and tools available, and be capable of immediately coming to the aid of any interior members who require assistance. The two in/ two out policy (#327) should always be followed.

Once additional companies or members arrive on the fireground, additional crews may be directed to the interior or rotate through positions; however, at least two standby members shall remain outside at all times.

Engine Company Operations (#328) should be referenced for additional information.